

Protekta Tile-N-Fix

A cementitious tile adhesive

DESCRIPTION

Protekta Tile-N-Fix is a ready to use composition of cement and special chemicals. It is an excellent non-shrink, self-curing, waterproofing, tile adhesive for fixing ceramic and mosaic tiles on horizontal and vertical surfaces.

USES

Can be used as adhesive for all types of tiles.

ADVANTAGES

- Ready to use
- Good bonding
- Good mechanical strength
- Curing is not required

APPLICATION

1. The surface should be clean and free from dust loose particles, oil and grease. Wet the surface by sprinkling water is essential.
2. Clean and dry the under surface of tile.
3. A patch test should be performed on the surface, prior to treatment.
4. Apply the paste on prepared surface to an approximate thickness of 3 mm (uneven surfaces may require more than 3 mm thickness) and comb the surface with a notched trowel.
5. Place tiles in position within 15 minutes of mixing and press firmly with twisting movements. Use damp cloth to remove excess paste from tile surface.
6. Tile joints may be filled by Protekta Tile-N-Grout following day.
7. Allow atleast 2 days of drying before

running water on tiles.

DOSAGE

2.0 to 2.5 kg /sq. mtr/ 3mm. thickness (of depending upon surface)

PACKING

25kg, 50kg (Other sizes available upon request)

SHELF LIFE

Six months in a closed uncontaminated container and should be utilized before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice. Product older than one year should be discarded.

STORAGE

Once opened, remaining material should be sealed and stored in a cool, dry place. Care should be taken to always keep product away from direct sunlight or extreme heat.

HEALTH & SAFETY

Non-hazardous, non-toxic, non-flammable

CAUTION

Add powder to water and prepare only required quantity to utilize within 15 minutes. Avoid fixing tiles outdoor when

rain is imminent, correct ratio of Protekta
Tile-N-Fix and water is essential for

optimum performance.

IMPORTANT NOTE : Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY: The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.



TECH-DRY (INDIA) PVT. LTD.

BUILDING PROTECTION SYSTEMS

877, 4th A Cross, 1st Stage, Indiranagar, Bangalore 560 038

Ph: 080-25255406 / 294 Fax: 080 - 25289159

e-mail: techdry@airtelmail.in, www.techdryindia.com

