

# Protekta Tile-N-Grout

**Is a cementitious tile grout**

## DESCRIPTION

Protekta Tile-N-Grout is a cement based grout. Provided as a dry powder that can be made into a paste with water for use.

## USES

Can be used as grouts for all type of joints in tiles, granite and marbles

## ADVANTAGES

- Makes the joint waterproof
- Self-curing
- Non-shrink
- Excellent adhesive

## APPLICATION

1. Joint should be clean pre-wetted
2. Make a paste with water to achieve desired consistency and applied to joint.
3. A patch test should be performed on the surface, prior to treatment.
4. A patch test should be performed on the surface, prior to treatment.

## DOSAGE

4.0 to 2.5 kg /sq. mtr / 3mm. thickness

## PACKING

25kg, 50kg (Other sizes available upon request)

## SHELF LIFE:

Six months in a closed uncontaminated container and should be utilized before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice. Product older than one year should be discarded.

## STORAGE:

Once opened, remaining material should be sealed and stored in a cool, dry place. Care should be taken to always keep product away from direct sunlight or extreme heat.

## CAUTION

Add powder to water, prepare only required quantity to utilize within 15 minutes. Avoid fixing tiles outdoor when rain is imminent, correct ratio of Protekta Tile-N-Grout and water is essential for optimum performance.

## HEALTH & SAFETY:

Non-hazardous, non-toxic, non-flammable

**IMPORTANT NOTE:** Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

**WARRANTY:** The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.



**TECH-DRY (INDIA) PVT. LTD.**  
BUILDING PROTECTION SYSTEMS  
# 877, 4<sup>th</sup> A Cross, 1<sup>st</sup> Stage, Indiranagar, Bangalore 560 038  
Ph: 080-25255406 / 294 Fax: 080 - 25289159  
e-mail: [techdry@airtelmail.in](mailto:techdry@airtelmail.in), [www.techdryindia.com](http://www.techdryindia.com)



an ISO 9001 : 2008 company